VAISALA HMP155 | TEMPERATURE & RELATIVE HUMIDITY

OUTPUT: 0...1V

-40...+60°C

0...100%

CABLE

Signal cable up to 3.5 meter length: **6x0.5 mm² + shield**. For longer cable, please consult sensor manufacturer.

SENSOR WIRING TABLE

Sensor	Sensor Pin			Kintech		Orbit 360			EOL Zenith	
Model	Manı	ufacturer	Cable Colors	Cab	le Colors	Section	Terminal	Туре	Section	Terminal
	•	Green	Ref	•	Green	Analog Channels	47 51 55 59 64 68 72 76 80 87	(-)	Analog Inputs	-
₩		White	Temp (+)		Yellow	Analog	48 52 56 60 65 69 73 77 81 84	Signal	Analog Inputs	1 2 3 4 5
		winte	remp (+)		rellow	Channels	85 86 99 92		Extra Analog	1 2 3 4 5 6 7 8
	•	Blue	Supply (+)		Pink	Analog Channels	49 53 57 61 66 70 74 78 82 88	*(+)	BAT	E .
		Yellow	DIT(1)		Crov	Analog	48 52 56 60 65 69 73 77 81 84 85 86 90 91 92	Signal	Analog Inputs	1 2 3 4 5
		rellow	RH (+)		Grey	Channels			Extra Analog	1 2 3 4 5 6 7 8
	•	Red	Supply (-)		Brown	Analog Channels	47 51 55 59 64 68 72 76 80 87	(-)	BAT	-
		Shie	eld		Yellow Green	Power Input	BAT	<u></u>	BAT	<u></u>

Note:

Data logger hardware version < 3, (+) = Bat+ with current limited (12mA). Only 1 sensor must be powered on each output terminal. Data logger hardware version ≥ 3 , (+) = Bat+ with current limited (50mA). Only 1 sensor must be powered on each output terminal.

REQUIRED DATA LOGGER VERSION

Minimum data logger required: **ORBIT 360 BASIC PLUS**.

Minimum **firmware** required: **2.40**. If your data logger has an older firmware version (<2.40), please configure the sensor as a generic sensor (voltage) in both Atlas software and the data logger. Remember to fill in both the slope and the offset for both the temperature and the humidity sensor.

HOW TO CONFIGURE IN ATLAS

Start Atlas and open the data logger you are working on. Now go to *Site settings* and scroll down to the *Channels* section and select the following type and model:

Group: Analog channels

Sensor Type: Temperature

Sensor Model: Vaisala HMP155

Group: Analog channels

Sensor Type: Relative Humidity

Sensor Model: Vaisala HMP155

Important! Please make sure you are working with the latest version of Atlas. To check for new updates click the *Check for updates* button in the left-hand menu located in the main dashboard.



VAISALA HMP155 | TEMPERATURE & RELATIVE HUMIDITY

OUTPUT: 0...1V

-40...+60°C

0...100%

HOW TO CONFIGURE THIS SENSOR ON SITE

We recommend performing the entire sensor configuration using Atlas at the office before installing sensors onsite. Once the sensor is correctly setup in Atlas, use the *Upload settings* tool, to upload the sensor configuration to the data logger. In case you are already on site and need to configure the sensor directly on the data logger, follow these steps:

- 1. Turn on the data logger.
- 2. Using the keypad on the data logger, navigate the menu until you see *Sensor model*, then click the "right arrow" on the keypad.
- 3. Now scroll down to the channel you are going to connect the sensor to, and click the "right arrow" on the keypad.
- 4. Now click "Set" on the keypad and scroll up in the menu to set the sensor model type according to the table here below. Once you have found the correct sensor model, click the "right arrow" key twice to select it and save.
- 5. Click the "left arrow" several times to go back to the main menu.

Data la seas madel	Firmware version	Sensor model type on data logger					
Data logger model	Firmware version	Magnitude	Number	Name			
	< 2.40	Temperature	01	milliVolts			
ORBIT 360	< 2.40	Relative humidity	01	milliVolts			
ORDIT 300	> 2.40	Temperature	06	TEMP VAISALA HAMP155			
	≥ 2.40	Relative humidity	38	HUM VAISALA HAMP155			
EOL ZENITH	201/	Temperature	01	miliVolts			
EOLZENITH	any	Relative humidity	01	miliVolts			

Keep in mind: if the sensor channel has been configured as milliVolts, the output values on data logger display will always be shown in milliVolts. Remember to fill in both the slope and the offset for both the temperature and the humidity sensor to see real sensor values in ${}^{\circ}$ C and ${}^{\circ}$ C in your datasets during a real-time connection with the data logger (from either Atlas or Atlas Mobile).

HOW TO CONFIGURE IN EOL MANAGER

Open EOL Manager and go to *Settings* of the data logger you are working on. Open the *Inputs* tab and select the following type and model:

TEMPERATURE

Group: Analog Inputs Sensor Type: Voltmeter

Sensor Model: Generic Voltimeter

Slope: 100Offset: -40

RELATIVE HUMIDITY

Group: Analog Inputs Sensor Type: Voltmeter

Sensor Model: Generic Voltimeter

Slope: 100Offset: 0

